



MODEL 3350DX SUPERDUTY DELUXE



The "SuperDuty Deluxe"

The Superduty Deluxe 48" Sheet Slitters offers many extra features for this multi-cutting equipment. To better serve the processor requiring a wider range of capacities, the Superduty Deluxe comes with a built in entry guide, stripper rings and intergraded scale to help the operator in setting up the cuts. It has the end housings with the legs integrated into them. The 3350DX "SuperDuty Deluxe is equipped with a ¾ HP motor with standard 110 V plug-in services to supply the torque required to cut a wide range of material thickness (16 gauge through 30 gauge) at a standard operating speed of 60 FPM. Two sets of tooling and Stripper Rings come standard on this slitter. The Stripper Rings are beneficial for light gauge pre-painted material to prevent marking the surface.



Standard features include:

- ⊕ 3" diameter cold-roll turned, ground and polished shafts mounted in dual wall ball bearings
- ⊕ Bearing are lubricated for life series
- ⊕ Gauge mounting on each side permits left or right hand operation
- ⊕ End frames have legs integrated into them for a more stable machine
- ⊕ The exclusive GARY Torsion Tube Assembly makes it a lightweight rugged unit
- ⊕ Heavy gauge steel table with a slotted top and quick-adjust entry guide
- ⊕ Slitter knives are proven GARY "Quickset" design manufactured from toolsteel
- ⊕ Knives are "reversible", intervals between sharpening is double that of a single edge knives
- ⊕ 2 sets of standard 3" x 5" x ¾" wide high-carbon tooling is included
- ⊕ 60 FPM standard operating speed
- ⊕ Heavy duty roller chain drive powered by ¾ HP gearmotor with thermal overload
- ⊕ Stripper rings to help prevent marking on pre-painted materials
- ⊕ Standard 110/220 V -1 Phase; **OPTIONAL:** 240-480/3 phase; or Variable Speed Controller

***The affordable
GARY SLITTER ...
Don't settle for anything less!***

Contact your machinery dealer and ask him for a demonstration. If you don't have a dealer or supplier in your area, feel free to contact us direct. We'll be glad to answer any questions you may have.

GARY MACHINERY LLC
1931 East Main Street
Griffith, IN 46319

**Phone: 219/ 980-5700
FAX: 219/ 980-0405**

www.GaryMachinery.net



MODEL 3351
THRIFTY
48" SLITTER



MODEL 3350 DX
"SUPERDUTY DELUXE"
48" SLITTER

WIDTH OVERALL	58"	WIDTH OVERALL	58"
WIDTH BETWEEN FRAMES	50 ⁵ / ₁₆ "	WIDTH BETWEEN FRAMES	52 ¹ / ₄ "
MAXIMUM SHEET WIDTH	49 ⁵ / ₁₆ "	MAXIMUM SHEET WIDTH	48 ¹ / ₂ " OR 51" LESS GAUGE
STANDARD TABLE HEIGHT	35"	STANDARD TABLE HEIGHT	35"
DEPTH OVERALL	28"	DEPTH OVERALL	26"
ARBOR DIAMETER	3"	ARBOR DIAMETER	3"
KNIFE DIMENSIONS	5" O.D. x ³ / ₄ "	KNIFE DIMENSIONS	5" O.D. x ³ / ₄ "
MOTOR HP	1/3 HP	MOTOR HP	³ / ₄ HP
FEED SPEED (FPM)	40 FPM	FEED SPEED (FPM)	60 FPM
VOLTAGE	110V - 1 PH.	VOLTAGE	110V / 220V - 1 PH.
WEIGHT	510 LBS.	WEIGHT	515 LBS.

Slitter Capacity - Number of cuts

Thickness			MODEL	
			3351 Thrifty	3350DX Super Duty Deluxe
Ga.	In.	Mm.		
30	.015"	.30	6	12
28	.018"	.37	4	8
26	.021"	.45	3	6
24	.027"	.60	3	4
22	.033"	.75	2	4
20	.039"	.91	2	3
18	.051"	1.2	1	2
16	.063"	1.5	1	1

* Cutting capacity is limited by allowable number of knives on the machine.

